



**Specification:**

Impedance: 50ohm  
 Frequency: DC-11GHz  
 Connector: N type Male  
 Cable type: LMR400, RG213, RG214

**MECHANICAL SPECIFICATIONS**

Connectors Brass ( Tri Alloy Plating )  
 Male Pin Brass Gold Plated  
 Female Pin Beryllium Copper Gold Plated  
 Temp Range -55\*~ +155\*  
 Dimensions D22.5mm x 31.3mm  
 Weight 60g

**RACOMTECH PTY LTD**  
 web: www.racomtech.com ABN: 51687385403  
 Tel: +64-3-88029296  
 Fax: +64-3-88027695  
 email: sales@racomtech.com.au  
 info@racomtech.com

TOLERANCE GROUP (UNLESS NOTED OTHERWISE)	
LINEAR	ANGULAR
X = ±0.5	X* = ±1.0°
XX = ±0.2	XX* = ±0.5°
XXX = ±0.05	XXX* =

TITLE		DRAWING	
RF COAXIAL N TYPE CONNECTOR		DATE	DWG
CRIMP PLUG FOR LMR400, RG213		01-08-2013	
MATERIAL		DRG. CHECK	
FINISH		MECH. CHECK	
SCALE		ELEC. CHECK	
1:1		APPROVED	
SHEET No. 1 OF 1		* DIMENSIONS IN MILLIMETERS UNDO * DRAWINGS PRACTICES TO AS 1100 * DO NOT SCALE * IF IN DOUBT/ASK	
PARTS No.		01-0317	
		A4	